

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Commercial name: Potassium metasilicate liquid ( $K_2SiO_3$ ), Alkon K 100

Registration number: 01-2119456888-17-0012

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Profession application: as an industrial degreasing agent for a degreasing in the food industry, degreasing of metal parts and equipment, in the glass industry

#### 1.3 Details of the supplier of the safety data sheet

Producer/importer: **Vodní sklo, a. s.**, Krakovská 1346/15, 110 01 Praha 1 – Nové Město

Address: Dornych 47, 656 16 Brno; U Tonasa 172/2, 403 31 Ústí nad Labem  
IČ 279 21 662

Telephone number: +420 530 530 000 (Brno), +420 475 245 362, +420 475 245 233 (Ústí)

Fax number: +420 530 530 002 (Brno), +420 475 507 164 (Ústí)

Competent person responsible for the SDS: Ing. Andrea Kudrová e-mail: andrea.kudrova@vodnisklo.cz

#### 1.4 Emergency telephone number

Toxikologické informační středisko (Poison center), Na Bojišti 1, 120 00 Praha 2;

Telephone number (24 hours/day) +420 224 919 293; +420 224 915 402

### 2. Hazards identification

#### 2.1 Classification of the substance or mixture

According to the Regulation (EC) No. 1272/2008:

The human health and environmental hazards:

Met. Corr. 1: H290. Skin Corr. 1B/Eye Dam. 1: H314.

May be corrosive to metals. Causes severe skin burns and eye damage.

Full text of the H, P phrases is listed in the section 16 of this safety data sheet.

#### 2.2 Label elements

Hazard pictogram(s):



Signal word:

**Danger**

Hazard statement(s):

H290 – May be corrosive to metals.

H314 – Causes severe skin burns and eye damage.

Precautionary statement(s) (prevention):

P262 – Do not get in eyes, on skin, or on clothing.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

### Precautionary statement(s) (response):

P301+P330+P331 – IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 – IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Precautionary statement(s) (storage):

P406 – Store in corrosive resistant/stainless steel or plastic container with a resistant inner liner.

### 2.3 Other hazards


The substance does not fulfill the criteria for PBT or vPvB substance.

No additional hazards had been determined.

## 3. Composition/information on ingredients

### 3.1 Substances

3.1.1 For substances classified according to the Regulation (EC) No. 1272/2008 is indicated

Chemical name:	Potassium metasilicate
Concentration in (%):	≤ 54 %
Hazard pictogram(s):	
Signal word:	<b>Danger</b>
Code of hazard class and hazard category:	Met. Corr. 1 Skin Corr. 1B/Eye Dam. 1
Hazard statement(s):	H290 H314
Precautionary statement(s) according to the CLP regulation:	P262 P280 P301+P330+P331 P303+P361+P353 P305+P351+P338 P406
CAS number:	1312-76-1
EC (EINECS) number:	215-199-1

Full text of the H, P phrases is listed in the section 16 of this safety data sheet.

### 3.2 Mixtures

Not applicable - it is not a mixture.

## 4. First aid measures

### 4.1 Description of first aid measures

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

First aid personnel must take care their own safety. In case of accident or if you feel unwell, or in case of the occurrence of any symptoms or doubts, consult your health condition with a doctor and provide information from this safety data sheet. Ensure the functioning of the vital functions (artificial respiration, inhalation of oxygen, heart massage). In case of unconsciousness place the affected person into the stabilized position on the side and do not administer any oral products.

Following aspiration/inhalation:

For liquid water glasses are not required any special measures.

Following skin contact:

Immediately remove contaminated clothing and shoes and wash affected areas with plenty of water, attach a sterile cover and seek out medical attention.

Following eye contact:

Remove contact lenses, if present and easy to do. Rinse eyes with pure fresh running water stream for at least 15 minutes while holding eyelids apart and seek out immediately medical attention. Continue rinsing during the affected person transport.

After ingestion:

Rinse mouth with water, drink plenty of water. Do not induce vomiting! Seek out immediately medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

Causes burns. May cause permanent eye damage. Potassium metasilicate liquid (MP = 1,0) is not acutely toxic via the oral, dermal or inhalation route. There are no fears of adverse systemic effects, because the major health hazard are local effects (pH-effect).

### 4.3 Indication of any immediate medical attention and special treatment needed

Seek out immediately medical attention.

## 5. Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media: Water, foam. The product is not combustible. The type of extinguishing agent to adapt the surrounding area.

Unsuitable extinguishing media: Not applicable.

### 5.2 Special hazards arising from the substance or mixture

Avoid inhalation of combustion fumes. Strongly alkaline, it is necessary to avoid contact of substance with skin and mucous membranes.

### 5.3 Advice for firefighters

Firefighters equip with breathing apparatus, adequate to environmental conditions, independent of the surrounding atmosphere and adequate protective clothing.

## 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Avoid direct contact with the leaking substance. Avoid contact with eyes and skin. Follow the instruction in section 8. Wear protective clothing, protective gloves, eyes/face protection, a container with pure water for washing out eyes should be placed in the workplace.

#### 6.1.2 For emergency responders

See section 6.1.1.

### 6.2 Environmental precautions

Prevent a penetration into soil, drainage, surface waters or groundwater.

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

### 6.3 Methods and material for containment and cleaning up

#### 6.3.1 Advices how to contain a spilled substance or mixture

Prevent a leakage; place the damaged packaging in the emergency containers. In case of a bigger amount of leakage, to create barriers, cover drains.

#### 6.3.2 Advices how to clean-up a spilled substance or mixture

The leaked substance to drain away or fill up by a suitable absorption material, for example by the universal sorbent, sand, sawdust. Place the waste at a safe place and ensure a disposal in accordance with the waste legislation as stated in section 13. Remove small remains by dissolving in hot water. In the case of entry into water-courses, drains, contamination of soil/vegetation inform immediately firefighters and the police.

#### 6.3.3 Any other information relating to spills and releases

Not applicable.

### 6.4 Reference to other sections

Personal protective means are listed in section 8. Disposal instructions are listed in section 13.

## 7. Handling and storage

### 7.1 Precautions for safe handling

Follow working instructions. Read the label (etiquette) before using. Avoid contact with eyes, skin and clothing. Wash hands and face thoroughly after the work. Beware of smoking, eating and drinking at the place of usage and storage of material. Prevent spills and penetration into drains. Employees shall wear protective working clothing, shoes, gloves, goggles.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in well-closed original containers, alkali-resistant (plastic, steel), in a dry rooms at the temperature above 0°C. Keep out of the reach of children. Do not store together with food, beverages and feed. Do not store in aluminum, copper, zinc, tin and their alloys, brass, fiberglass and galvanized materials containers. Time period of workability is 1 year in case of compliance with storage and transport conditions.

### 7.3 Specific end use(s)

Is listed in section 1.2.

## 8. Exposure controls/personal protection

### 8.1 Control parameters

**PNEC:** 7,5 mg/l (fresh water), 1 mg/l (marine water), 7,5 mg/l (water - intermittent releases), 348 mg/l (sewage treatment plant)

**DNEL:** workers: Long-term exposure - systemic effects, Dermal: 1,49 mg/kg/day  
workers: Long-term exposure - systemic effects, Inhalation: 5,61 mg/m<sup>3</sup>  
general population: Long-term exposure - systemic effects, Dermal: 0,74 mg/kg/day  
general population: Long-term exposure - systemic effects, Inhalation: 1,38 mg/m<sup>3</sup>  
general population: Long-term exposure - systemic effects, Oral: 0,74 mg/kg/day

#### Occupational exposure limits in the working environment

Czech Republic (Government Regulation No. 361/2007 Coll., as amended by valid act): No Occupational Exposure Limit. Occupational exposure limit: **Permissible Exposure Limit (PEL)** = 1 mg/m<sup>3</sup>, **Maximum permissible concentration (NPK-P)** = 2 mg/m<sup>3</sup> (15 min TWA) is recommended on the basis of analogy with potassium hydroxide.

European Union (Directive No. 2006/15/EC and No. 2009/161/EU): not determined.

### 8.2 Exposure controls

8.2.1 Appropriate engineering controls

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

Work in a well-ventilated room. Follow the usual measures of health protection while working with chemical substances and mixtures, especially avoid ingestion and contact with the respiratory organs, eyes and skin. I.e. do not eat, drink and smoke while working. Wash your hands with warm water and soap before and after working. Treat your skin with appropriate protection creams. Personal protective equipment is recommended.

### 8.2.2 Individual protection measures, such as personal protective equipment

- a) Eye/face protection – safety goggles or face-shield
- b) Skin protection
  - Hand protection – protective rubber gloves,
  - Other – protective working clothing, protective shoes,
- c) Respiratory protection – it is not necessary,
- d) Thermal hazards – not applicable (substance does not represent thermal hazard).

The manufacturer's instructions for using of personal protective equipment must be fulfilled.

### 8.2.3 Environmental exposure controls

Proceed in accordance with the valid legislation for the air and water protection. The primary danger of potassium metasilicate liquid (MP = 1,0) is alkalinity. Avoid release into the environment, capture the leakage.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

a) appearance	a clear or slightly turbid viscous liquid
b) odour	odourless
c) odour threshold	not determined
d) pH	13,5 – 14,0
e) melting point/freezing point	-3°C
f) initial boiling point and boiling range	101–102°C
g) flash point	not determined
h) evaporation rate	not determined
i) flammability (solid, gas)	not flammable (liquid)
j) upper/lower flammability or explosive limits	not determined
k) vapour pressure	not determined
l) vapour density	not determined
m) relative density	1 600 –1 640 kg/m <sup>3</sup>
n) solubility(ies)	freely mixed with water, insoluble in fats
o) partition coefficient n-octanol/water	not determined
p) auto-ignition temperature	not determined
q) decomposition temperature	not determined
r) viscosity	20 –150 mPa.s
s) explosive properties	not determined
t) oxidising properties	not determined

### 9.2 Other information

Not determined.

## 10. Stability and reactivity

### 10.1 Reactivity

Beware of following conditions: In case of compliance with storage requirements the substance is stable. While working is necessary to follow the standards of safety and health protection at work.

Beware of following materials: acids, ammonium salts (generation of ammonia gas), metals – corrosion.

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

### 10.2 Chemical stability

In case of compliance with standard storage and handling conditions the substance is stable.

### 10.3 Possibility of hazardous reactions

It must not come into contact with aluminum, zinc, lead, tin and their alloys - dissolves them slowly to generate hydrogen, which creates an explosive mixture with the air.

### 10.4 Conditions to avoid

Do not allow the material to freeze. Avoid compounding with mineral acid.

### 10.5 Incompatible materials

It must not come into contact with aluminum, zinc, lead, tin and their alloys - dissolves them slowly to generate hydrogen, which creates an explosive mixture with the air.

### 10.6 Hazardous decomposition products

Hydrogen during the reaction with metals.

## 11. Toxicological information

### 11.1 Information on toxicological effects

#### 11.1.1 Substances (potassium metasilicate)

- acute toxicity – all the symptoms of acute toxicity are caused by high alkalinity, the material will cause chemical burns: LD<sub>50</sub>, oral, rat: 1 152 to 1 349 mg/kg; LD<sub>50</sub>, dermal, rat: > 5 000 mg/kg;
- skin corrosion/irritation – corrosivity, in case of contact threatens strong burns to skin and mucous membranes;
- serious eye damage/irritation – corrosivity, in case of entering into eyes may cause permanent eye damage;
- respiratory or skin sensitisation – undetected;
- germ cell mutagenicity – undetected – negative in vitro/in vivo;
- carcinogenicity – undetected;
- reproductive toxicity – undetected;
- STOT - single exposure – undetected;
- STOT - repeated exposure – not classified – NOAEL oral (180 d, rat): 159 mg/kg/day;
- aspiration hazard – undetected.

#### 11.1.2 Mixtures

- acute toxicity – it is not a mixture;
- irritation – it is not a mixture;
- corrosivity – it is not a mixture;
- sensitisation – it is not a mixture;
- repeated dose toxicity – it is not a mixture;
- carcinogenicity – it is not a mixture;
- mutagenicity – it is not a mixture;
- toxicity for reproduction – it is not a mixture.

#### 11.1.3 Undetected.

#### 11.1.4 Potassium metasilicate liquid (MP = 1,0) etches the skin and mucous membranes and in case of entering into eyes may cause permanent eye damage.

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

- 11.1.5 Undetected.
- 11.1.6 The substance is classified as corrosive to skin and eyes.
- 11.1.7 Information on likely routes of exposure  
Skin/eye exposure, ingestion (by swallowing) – for effects see section 11.1.4.
- 11.1.8 Symptoms related to the physical, chemical and toxicological characteristics  
For effects see section 11.1.4.
- 11.1.9 Delayed and immediate effects and also chronic effects from short and long-term exposure  
For effects see section 11.1.4 - strong burns to skin and mucous membranes and serious eye damage.
- 11.1.10 Interactive effects  
Undetected.
- 11.1.11 Absence of specific data  
If some of the information are not listed in section 11, they were not available.
- 11.1.12 Mixture versus substance information  
Undetected.
- 11.1.13 Other information  
Not applicable.

## 12. Ecological information

### 12.1 Toxicity

Ecotoxicity	
LC <sub>50</sub> (96 h, <i>Brachydanio rerio</i> ) for freshwater fishes:	210 mg/l
EC <sub>0</sub> (30 min, <i>Pseudomonas putida</i> ) for microorganisms:	1 000 mg/l
EC <sub>50</sub> (3 h, <i>activated sludge</i> ) for microorganisms:	> 100 mg/l

### 12.2 Persistence and degradability

Not applicable to the inorganic substances - cannot be removed from the water by biological cleaning processes.  
CHSK and BSK not determined.

### 12.3 Bioaccumulative potential

None. Silicates are used physiologically by algae and plants without retention.

### 12.4 Mobility in soil

Not determined.

### 12.5 Results of PBT and vPvB assessment

Potassium metasilicate liquid (MP = 1,0) is not classified as a PBT or vPvB substance.

### 12.6 Other adverse effects

According to the Water Act No. 254/2001 Coll., as amended by valid act, the product is considered a defective substance. The alkalinity of the substance will have a local impact on the ecosystems sensitive to the pH changes.

## 13. Disposal considerations

### 13.1 Waste treatment methods

Reuse or disposal in accordance with valid legislation related to waste.

Recommended classification according to the catalogue: 16 05 07 (discarded inorganic chemicals, which are or contain hazardous substances).

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

Recommended disposal methods for a contaminated packaging:

When disposal the valid legislation for the hazardous waste treatment according to the categorization and the Waste Catalogue shall be followed.

Waste code:

15 01 10 – for packaging containing residues of hazardous substances or packaging contaminated by such substances,

15 02 02 – for absorbents, filtration materials, cleaning fabrics and protective clothing contaminated by hazardous substances.

After a thorough rinse of the original content with warm water can be empty packaging removed according to the packaging type under codes 150102 - plastic packaging category "O" (plastic canisters, drums), 150104 - metal packaging category "O" (metal barrels) or 150106 - composite packaging category "O" (the IBC containers).

Measures for the exposure control for the waste treatment:

Disposal of the substance and packaging should be proceed in accordance with valid legislation for personal, atmosphere and water precaution.

The legislation on the waste:

Czech Republic

Act No. 185/2001 Coll., on waste and amending some other Acts, as amended by valid act.

Decree of the Ministry of Environment No. 381/2001 Coll., which determines the Waste Catalogue, as amended by valid act.

European Union

Directive No. 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives (Text with EEA relevance).

Council Directive No. 91/689/EEC of 12 December 1991 on hazardous waste as amended by Directives No. 94/31/EC of 27 June 1994 and No. 2008/98/EC of the European Parliament and of the Council of 19 November 2008 and Regulation (EC) No. 166/2006 of the European Parliament and of the Council of 18 January 2006.

## 14. Transport information

### 14.1 UN number

UN number – ground transport: 3266

### 14.2 UN proper shipping name

UN name: corrosive liquid, basic, inorganic, N.O.S.

### 14.3 Transport hazard class(es)

Hazard class 8 – corrosive substances.

### 14.4 Packing group

Packing group - III

### 14.5 Environmental hazards

According to the Water Act No. 254/2001 Coll., as amended by valid act, the product is considered a defective substance. The alkalinity of the substance will have a local impact on the ecosystems sensitive to the pH changes. It is not classified as a marine pollutant.

### 14.6 Special precautions for user

The substance is classified as corrosive to skin and eyes. Avoid contact with eyes and skin. Unsuitable packaging: aluminum, zinc, lead, tin and their alloys.

### 14.7 Transport in bulk according to Annex II MARPOL 73/78 and the IBC code

Not determined – not applicable.

## 15. Regulatory information



# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations: Water endangering class 1 (a little danger to the water, Germany)

#### Czech Republic

Act No. 258/2000 Coll., on the protection of public health and amending some related Acts, as amended by valid act.

Government Regulation No. 361/2007 Coll., which stipulates the conditions of health protection at work, as amended by valid act.

Act No. 350/2011 Coll., on the chemical substances and chemical mixtures and amending some Acts (chemical Act), as amended by valid act.

Act No. 185/2001 Coll., on waste and amending some other Acts, as amended by valid act.

Decree of the Ministry of Environment No. 383/2001 Coll., on details of waste disposal, as amended by valid act.

Act No. 477/2001 Coll., on packaging and amending some related Acts (Act on Packaging), as amended by valid act.

#### European union

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive No. 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive No. 76/769/EEC and Commission Directives No. 91/155/EEC, No. 93/67/EEC, No. 93/105/EC and No. 2000/21/EC, as amended by valid act.

Regulation (EC) No. 689/2008 of the European Parliament and of the Council of 17 June 2008 concerning the export and import of dangerous chemicals, as amended by valid act.

Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives No. 67/548/EEC and No. 1999/45/EC, and amending Regulation (EC) No. 1907/2006 (Text with EEA relevance), as amended by valid act.

Council Regulation (EC) No. 440/2008 of 30 May 2008 laying down test methods pursuant to Regulation (EC) No. 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (Text with EEA relevance), as amended by valid act.

Directive No. 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives (Text with EEA relevance).

Council Directive No. 91/689/EEC of 12 December 1991 on hazardous waste as amended by Directives No. 94/31/EC of 27 June 1994 and No. 2008/98/EC of the European Parliament and of the Council of 19 November 2008 and Regulation (EC) No. 166/2006 of the European Parliament and of the Council of 18 January 2006.

Council Directive No. 94/55/EC of 21 November 1994 on the approximation of the laws of the Member States with regard to the transport of dangerous goods by road.

Council Directive No. 96/49/EC of 23 July 1996 on the approximation of the laws of the Member States with regard to the transport of dangerous goods by rail.

Council Directive No. 89/391/EEC of 12 June 1989 on the introduction of measures to encourage improvements in the safety and health of workers at work.

Council Directive No. 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive No. 89/391/EEC).

Commission Directive No. 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive No. 98/24/EC and amending Directives No. 91/322/EEC and No. 2000/39/EC (Text with EEA relevance).

Commission Directive No. 2009/161/EU of 17 December 2009 establishing a third list of indicative occupational exposure limit values in implementation of Council Directive No. 98/24/EC and amending Commission Directive No. 2000/39/EC (Text with EEA relevance).

Council Directive No. 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances.

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

Commission Regulation (EU) No. 453/2010 of 20 May 2010 amending Regulation (EC) No. 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (Text with EEA relevance).

### 15.2 Chemical safety assessment

Chemical safety assessment for the substance has been carried out by the producer.

## 16. Other information

### Statement:

Safety Data Sheet has been prepared in accordance with Regulations (EC) of the European Parliament and of the Council No. 1907/2006 and No. 1272/2008 and Commission Regulation (EU) No. 453/2010. This product shall be stored, handled and used with good hygiene practices of industry and in accordance with valid legislation. These information does not substitute the quality specification and cannot be considered as a guarantee of the suitability and applicability of this product for a specific application. The mentioned information correspond to a current state of knowledge and experiences and are in accordance with valid legislation. The customer is responsible for compliance with the valid regional legislation.

### Sources of data used to compile the safety data sheet:

Safety Data Sheet for Sodium metasilicate pentahydrate, Potassium water glass liquid (MP ≤ 1,6), material CEES „Soluble silicates“ of June 2011, Chemical safety report: Silicic acid, Potassium salt, Vodní sklo, a.s.

### Danger, Warning:

GHS05 danger

### Wording of H-phrases, P-phrases:

### Hazard statement(s) according to sections 2 and 3:

H290 – May be corrosive to metals.

H314 – Causes severe skin burns and eye damage.

### Precautionary statement(s) according to sections 2 and 3:

#### Prevention:

P262 – Do not get in eyes, on skin, or on clothing.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

#### Response:

P301+P330+P331 – IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 – IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### Storage:

P406 – Store in corrosive resistant/stainless steel or plastic container with a resistant inner liner.

Met.Corr.1: substance or mixture corrosive to metals, hazard category 1

Skin Corr.1B: skin corrosion, hazard category 1B

Eye Dam. 1: serious eye damage, hazard category 1

BL Safety Data sheet SDS  
DNEL Derived no-effect level  
EC<sub>50</sub> median effective concentration  
LD<sub>50</sub> median lethal dose  
LC<sub>50</sub> median lethal concentration  
NOEC no observable effect concentration  
NOAEL no observed adverse effect level

# Safety data sheet

According to the Commission Regulation (EU) No. 453/2010

Date of issue: 25. 8. 2012

Revision Date: 31. 5. 2015

## Potassium metasilicate liquid (MP = 1,0)

NPK-P	maximum permissible concentration
PBT	Persistent, bioaccumulative and toxic
PEL	permissible exposure limit
PNEC	Predicted no-effect concentration
STOT	Specific Target Organ Toxicity
TWA	time weighted average
vPvB	Very persistent, very bioaccumulative

### Instructions for training:

Persons who handling the product shall be instructed about the handling hazards and requirements for the health and environment precaution (see the appropriate provisions of the Labour Code).

### Access to information:

Each employer shall in accordance with Article 35 of the Regulation (EC) of the European Parliament and of the Council No. 1907/2006 to provide access to the information from the safety data sheet to all personnel who use this product or are exposed to its effects at work, as well as to their representatives.

**Revision:** 1<sup>st</sup> issue

**Revision:** 4. 3. 2013 – change of person responsible for the SDS

**Revision:** 31. 5. 2015 – remove the classification according to the Directives No. 67/548/EEC and No. 1999/45/EC

### The extent of responsibility:

Responsibilities of safety data sheet recipients (customers, users, distributors, etc.) is to ensure that the information contained therein are well understood by all personnel who may use, handle, dispose or in any way come into contact with the product. Information and instructions given in this safety data sheet are reliable, provided that the product is used under the prescribed conditions and in accordance with the designated uses listed on the packaging or in the Product Data Sheets. User is responsible for any other application of this product, including the application of this product in combination with any another product or any other processes. Hence the user is responsible for determination of appropriate safety measures and the implementation of legislation covering his own activities. This version of the safety data sheet replaces all previous versions.